

## GKB 209 Analog Camera

Vandalproof Dome Camera with Fixed Lens

GKB 209 is a compact dome camera provides high-quality image and vandalproof construction. It adopts Sony latest 1/3" CCD, GKB 209 prevents a 0.3-Lux low illumination and a clear and crispy image. The streamlined design and vandalproof casing could fit in with mostly architectural style, and prevent the camera damage from vandalism

### Features:

- **Sony Super-Had CCD II**  
Equipped with 1/3" Sony Super-Had CCD II, GKB 209 presents a quality 420 TV lines of resolution and higher S/N ratio.
- **3-Axis Inner Mechanism**  
GKB 209 analog camera adopts an inner 3-axis mechanism design, provides the installers with a wide range of camera angles and self-selection wall mount or ceiling mount installation.
- **Minimum Illumination 0.3 Lux**  
GKB 209 analog camera is with min. illumination at 0.3Lux (50 IRE, F1.4) and 0.01Lux(10 IRE, F1.4), it allows the camera to have clear image even under dim environment.
- **Weatherproof IP66 Rating**  
With metal construction housing, GKB 209 analog camera provides IP66 weatherproof standard.



# GKB 209 Analog Camera

Video	Image Sensor	1/3" Sony Super-HAD CCD II
	Effective Number of Pixels	NTSC: 510(H)×492(V) PAL: 500(H)×582(V)
	Resolution	420 TVL
	Min. Illumination	0.3Lux (50 IRE, F1.4); 0.01Lux(10 IRE, F1.4)
	Gamma	0.45
	S/N Ratio	>48dB
	Sync. Mode	Internal Sync.
	Scanning System	2:1 Interlace
	Horizontal Sync. Frequency	NTSC: 15.734 KHz / PAL: 15.625 KHz
	Shutter Control	NTSC: 1/60~1/100,000 sec PAL: 1/50~1/100,000 sec
	BNC Video Output	1.0 Vp-p, 75 ohm
	On-Screen Display	-
	ICR (IR-Cut Filter)	-
	Auto Electronics Shutter	On
	Auto Gain Control	On
	Back Light Compensation	On
	White Balance	ATW
	Power	Power Supply
Power Consumption		2W
Lens	6mm Fixed Lens	
Ingress Protection	IP 66	
Dimension	84(H) * 119(Ø) mm	
Weight	0.8 KG	
Mounting	Surface Mount	
Operating Temperature	-10°C ~ 60°C	

Dimension (mm)

