

GKB 209VF Analog Camera

Vandalproof Dome Camera with Varifocal Lens

GKB 209VF is a compact dome camera provides high-quality image and vandalproof construction. It adopts Sony latest 1/3" CCD, GKB 209VF prevents a 0.3-Lux low illumination and a clear and crispy image. The streamlined design and vandalproof casing could fit in with mostly architectural style, and prevent the camera damage from vandalism

Features:

- **Sony Super-Had CCD II**
Equipped with 1/3" Sony Super-Had CCD II, GKB 209VF presents a quality 420 TV lines of resolution and higher S/N ratio.
- **Minimum Illumination 0.3 Lux**
GKB 209VF analog camera is with min. illumination at 0.3Lux (50 IRE, F1.4) and 0.01Lux(10 IRE, F1.4), it allows the camera to have clear image even under dim environment.
- **Varifocal Lens**
GKB 209VF features a varifocal lens with a focal length of 3.7 ~12 mm that intuitively manages the amount of light passing through the lens for consistent image
- **3-Axis Inner Mechanism**
GKB 209VF analog camera adopts an inner 3-axis mechanism design, provides the installers with a wide range of camera angles and self-selection wall mount or ceiling mount installation.
- **Weatherproof IP66 Rating**
With metal construction housing, GKB 209VF analog camera provides IP66 weatherproof standard.



GKB 209VF Analog Camera

Video	Image Sensor	1/3" Sony Super-HAD CCD II
	Effective Number of Pixels	NTSC: 510(H)×492(V) PAL: 500(H)×582(V)
	Resolution	420 TVL
	Min. Illumination	0.3Lux (50 IRE, F1.4); 0.01Lux(10 IRE, F1.4)
	Gamma	0.45
	S/N Ratio	>48dB
	Sync. Mode	Internal Sync.
	Scanning System	2:1 Interlace
	Horizontal Sync. Frequency	NTSC: 15.734 KHz / PAL: 15.625 KHz
	Shutter Control	NTSC: 1/60~1/100,000 sec PAL: 1/50~1/100,000 sec
	BNC Video Output	1.0 Vp-p, 75 ohm
	On-Screen Display	-
	ICR (IR-Cut Filter)	-
	Auto Electronics Shutter	On
	Auto Gain Control	On
	Back Light Compensation	On
	White Balance	ATW
Power	Power Supply	DC 12V
	Power Consumption	2W
Lens	3.6mm / 6mm Varifocal Lens	
Ingress Protection	IP 66	
Dimension	84(H) * 119(Ø) mm	
Weight	0.8 KG	
Mounting	Surface Mount	
Operating Temperature	-10°C ~ 60°C	

Dimension (mm)

