

GKB 3103 Analog Camera

Dome camera with High Resolution CCD

GKB 3103 is a high resolution dome camera for use in indoor residential and small business surveillance installations. GKB 3103 delivers optional for audio and RCA Jack for customizing and dome case which is rotated 360 degree providing easy installation.

Features:

- **Additional RCA Jack**

GKB 3103 features optional RCA Jack. This allows installers to monitor images during installation for accurate and quick adjustment of the focus and viewing-angle.

- **Sony High Resolution CCD**

GKB 3103 incorporates Sony Super-Had CCD image sensor. It delivers high sensitivity levels and high picture quality.

- **360 Degree Swivel**

Dome case of GKB3103 is special designed as 360 degree swivel. Installers can separate the dome case easily and save much time in installation.

- **Optional for Audio**

An optional audio function provides customers who need one way audio for special environment.



GKB 3103 Analog Camera

Video	Image Sensor	1/3" Sony Super HAD CCD
	Total Number of Pixels	NTSC: 811(H) * 508(V) PAL: 795(H) * 596(V)
	Number of Effective Pixels	NTSC: 768(H) * 494(V) PAL: 752(H) * 582(V)
	Resolution	550 TV Line
	Min. Illumination	0.3 Lux, 50 IRE, F1.4 / 0.01 Lux, 10 IRE, F1.4
	Gamma	0.45
	S/N Ratio	>48 dB
	Sync. Mode	Internal Sync.
	Scanning System	2:1 Interlace
	Horizontal Sync. Frequency	NTSC: 15.734 KHz / PAL: 15.625 KHz
	Shutter Control	NTSC: 1/60 ~ 1/100,000 sec PAL: 1/50 ~ 1/100,000 sec
	BNC Video Output	1.0Vpp, 75 ohm
	Auto Electronics Shutter	On
	Auto Gain Control	On
	Line Lock	On (Available When AC Voltage is Used)
Power	Power Supply	12V~24V DC / 24V AC
	Power Consumption	3.6W
	Audio input / output	Optional
Lens	3.6 mm Board Lens (Standard); 4 mm, 6 mm, 8 mm, 12 mm (Optional)	
Dimension	120 (ø) * 83 (H) mm	
Weight	0.5 kg	
Mounting	Surface Mount	
Operating Temperature	-10°C ~ 60°C	

Dimensions

