

## GKB 3109 Analog Camera

Dome camera with Sony CCD

GKB 3109 is a basic dome camera for use in indoor residential and small business surveillance installations. GKB 3109 delivers optional for audio and RCA Jack for customizing and dome case which is rotated 360 degree providing easy installation.

### Features:

- **Additional RCA Jack**

GKB 3109 features optional RCA Jack. This allows installers to monitor images during installation for accurate and quick adjustment of the focus and viewing-angle.

- **High Performance Sony CCD**

GKB 3109 incorporates Sony CCD image sensor. It delivers high sensitivity levels and high quality picture.

- **360 Degree Swivel**

Dome case of GKB 3109 is special designed as 360 degree swivel. Installers can separate the dome case easily and save much time in installation.

- **Optional for Audio**

An optional audio function provides customers who need one way audio for special environment.



## GKB 3109 Analog Camera

Video	Image Sensor	1/3" Sony CCD
	Total Number of Pixels	NTSC: 537(H) * 505(V) PAL: 537(H) * 597(V)
	Number of Effective Pixels	NTSC: 510(H) * 492(V) PAL: 500(H) * 582(V)
	Resolution	420 TV Line
	Min. Illumination	0.3 Lux, 50 IRE, F1.4 / 0.01 Lux, 10 IRE, F1.4
	Gamma	0.45
	S/N Ratio	>48 dB
	Sync. Mode	Internal Sync.
	Scanning System	2:1 Interlace
	Horizontal Sync. Frequency	NTSC: 15.734 KHz / PAL: 15.625 KHz
	Shutter Control	NTSC: 1/60 ~ 1/100,000 sec PAL: 1/50 ~ 1/100,000 sec
	BNC Video Output	1.0Vpp, 75 ohm
	Auto Electronics Shutter	On
	Auto Gain Control	On
	White Balance	ATW
	Power	Power Supply
Power Consumption		3.6W
Audio input/output		Optional
Lens	3.6 mm Board Lens (Standard); 4 mm, 6 mm, 8 mm, 12 mm (Optional)	
Dimension	120 (ø) * 83 (H)mm	
Weight	0.5 kg	
Mounting	Surface Mount	
Operating Temperature	-10°C ~ 60°C	

## Dimensions

