

GKB 5008 Analog Camera

Weatherproof High Resolution Analog Camera with Infrared and board lens

GKB 5008 is an analog camera for use in outdoor surveillance systems. With 3-Axis bracket, GKB 5008 features easy installation and flexible adjustment for preferred angles.

Features:

- **Built-in Infrared**
Infrared sensors inside the camera's housing provide the ability to capture images during night and low-light conditions.
- **Weatherproof Housing**
IP66 Weatherproof housing allows GKB 5008 to be installed in most applications and environments. Strong metal casing and bracket provided added protection..
- **3-Axis Bracket**
3-Axis bracket smart design features easy installation and flexible adjustment for preferred angles which allows a rotation of 180° vertically and 360° horizontally.
- **Separated Protective Glass**
GKB 5008 features separated protective glass which avoid LED light reflection problem and blurring of images.



Bracket is Licensed by Hwan Ming Enterprise Co., Ltd.

Alternate Views



GKB 5008 Analog Camera

| | | |
|---------------------------|---|--|
| Video | Image Sensor | 1/3" Sony CCD |
| | Total Number of Pixels | NTSC: 811(H) * 508(V) / PAL: 795(H) * 596(V) |
| | Number of Effective Pixels | NTSC: 768(H) * 494(V) / PAL: 752(H) * 582(V) |
| | Resolution | 550 TV Lines |
| | Min. Illumination | 0.3 Lux, F1.2 |
| | Gamma | 0.45 |
| | S/N Ratio | >48 dB |
| | Sync. Mode | Internal Sync |
| | Scanning System | 2:1 Interlace |
| | Horizontal Sync. Frequency | NTSC: 15.734 KHz / PAL: 15.625 KHz |
| | Shutter Control | NTSC: 1/60 ~ 1/100,000 sec / PAL: 1/50 ~ 1/100,000 sec |
| | BNC Video Output | 1.0Vp-p.75ohm |
| | Night Mode | Auto |
| | Auto Electronics Shutter | ON-OFF |
| | Auto Gain Control | ON-OFF |
| Back Light Compensation | ON-OFF | |
| White Balance | ATW | |
| Infrared LED | Quantity | 28 |
| | Peak Wavelength | 850 nm |
| | Radiant Distance | 20 meter |
| Power | Power Supply | 12V DC |
| | Power Consumption | 4.2 W |
| Lens | 6 mm board lens (standard); 4mm/ 8 mm board lens (optional) | |
| Dimension | 118 (L) * 78 (Ø) mm | |
| Weight | 0.3 kg | |
| Ingress Protection Rating | IP66 | |
| Operating Temperature | -10°C ~ 60°C | |

Dimension (mm)

