

## GKB 5408 Analog Camera

HR Color Dome Camera with Fixed Lens

GKB 5408 is a compact dome camera provides high-quality image. It adopts Sony 1/3" Super-HAD CCDII , prevents a 0.3-Lux low illumination and a clear and crispy image. The streamlined design could fit in with mostly architectural style.

### Features:

- **550 TV Lines of Resolution**  
Equipped with 1/3" Sony Super-HAD CCDII, GKB 5408 presents a quality 550 TV lines of resolution and higher S/N ratio.
- **Black Light Compensation**  
GKB 5408 features BLC function to improve image detail of foreground objects in excessive background light conditions.
- **3-Axis Inner Mechanism**  
GKB 5408 analog camera adopts an inner 3-axis mechanism design, provides the installers with a wide range of camera angles and self-selection wall mount or ceiling mount installation.
- **Minimum Illumination 0.3 Lux**  
GKB 5408 analog camera is with min. illumination at 0.3Lux, F1.4, it allows the camera to have clear image even under dim environment.



## GKB 5408 Analog Camera

Video	Image Sensor	1/3" Sony Super HAD-CCD II
	Effective Number of Pixels	NTSC: 768(H)×494(V) PAL: 752(H)×582(V)
	Resolution	550 TVL
	Min. Illumination	0.3Lux, F1.4
	Gamma	0.45
	S/N Ratio	>48dB
	Sync. Mode	Internal Sync.
	Scanning System	2:1 Interlace
	Horizontal Sync. Frequency	NTSC: 15.734 KHz / PAL: 15.625 KHz
	Shutter Control	NTSC: 1/60~1/100,000 sec PAL: 1/50~1/100,000 sec
	BNC Video Output	1.0 Vp-p, 75 ohm
	Auto Electronics Shutter	On
	Auto Gain Control	On
	Back Light Compensation	On
White Balance	ATW	
Power	Power Supply	DC 12V
	Power Consumption	1.5W
Lens	3.6 mm Fixed Board Lens	
Ingress Protection	IP 44	
Dimension	118(Ø)*78(H) mm	
Weight	0.18 KG	
Operating Temperature	-10°C ~ 60°C / 30% ~ 80% RH	

Dimension (mm)

