

GKB 5408VR Analog Camera

HR Color Dome IR Camera with Varifocal Lens

GKB 5408VR is a compact dome camera provides high-quality image. It adopts Sony 1/3" Super-HAD CCD II, prevents a 0.3 Lux low illumination and a clear and crispy image. Smart LED design prevent over-exposure when subject is close to the camera. The streamlined design could fit in with mostly architectural style.

Features:

- **550 TV Lines of Resolution**
Equipped with 1/3" Sony Super HAD-CCD II, presents a quality 550 TV lines of resolution and higher S/N ratio.
- **Minimum Illumination 0.3 Lux**
GKB 5408VR analog camera is with min. illumination at 0.3Lux, F1.4, it allows the camera to have clear image even under dim environment.
- **Varifocal Lens**
The GKB 5408VR features a varifocal lens with a focal length of 3.7-12mm that intuitively manages the amount of light passing through the lens for consistent image brightness.
- **Smart IR Control**
GKB 5408VR features a Smart IR Control function. While the object is too close to the camera, the camera would automatically adjust its image to prevent IR over-exposure problem.
- **IR Range 20M**
GKB 5408VR features with 18pcs IR LED and latest Sony high sensitivity CCD, the IR radiance distance can reach 20M in outdoor environment.
- **3-Axis Inner Mechanism**
GKB 5408VR analog camera adopts an inner 3-axis mechanism design, provides the installers with a wide range of camera angles and self-selection wall mount or ceiling mount installation.



GKB 5408VR Analog Camera

Video	Image Sensor	1/3" Sony Super-HAD CCD II
	Effective Number of Pixels	NTSC: 768(H)×494(V) PAL: 752(H)×582(V)
	Resolution	550 TVL
	Min. Illumination	0.3Lux, F1.4, 0Lux when IR is ON
	Gamma	0.45
	S/N Ratio	>48dB
	Sync. Mode	Internal Sync.
	Scanning System	2:1 Interlace
	Horizontal Sync. Frequency	NTSC: 15.734 KHz / PAL: 15.625 KHz
	Shutter Control	NTSC: 1/60~1/100,000 sec PAL: 1/50~1/100,000 sec
	BNC Video Output	1.0 Vp-p, 75 ohm
	Auto Electronics Shutter	On
	Auto Gain Control	On
	Back Light Compensation	On
White Balance	ATW	
Infrared LED	Quantity	18
	Radiant Distance	20M
Power	Power Supply	DC 12V
	Power Consumption	3W
Lens	3.7~12mm Fixed Iris Varifocal Lens	
Ingress Protection	IP 44	
Dimension	118(∅)*78(H) mm	
Weight	0.22 KG	
Operating Temperature	-10°C ~ 60°C / 30% ~ 80% RH	

Dimension (mm)

