

GKB IC202/W PnP IP Camera

Plug-and-Play Indoor CMOS IP Camera

GKB IC202/W is a network-ready camera for indoor use in residential and small business surveillance installations. GKB IC202/W delivers plug-and-play (PnP) networking when used with GKB zIP View™ software, and this all-in-one design features compact housing and built-in microphone.

Features:

- **Plug & Play**

GKB IC202/W is a plug & play IP camera that makes network set-up easy. Once installed, set-up is as simple as entering ID and password using GKB zIP View™ software.

- **MPEG4 Video Compression**

GKB IC202/W features MPEG4 video compression for superior video quality. Image quality is enhanced by avoiding the conversion of analog signal to digital before transmission.

- **3G Mobile Access**

GKB IC202/W enables 3G mobile surveillance by RTSP. With mobile version NVR, surveillance is done by simply entering ID and password, on most mobile phone of Windows Mobile, Symbian, and iPhone OS.

- **Built-in Microphone**

GKB IC202/W features built-in microphone for simultaneous surveillance of video and audio.



GKB IC202/W PnP IP Camera

Video	Image Sensor	1/4" CMOS
	Number of Effective Pixels	640(H) * 480(W)
	Video Compression	MPEG4
	Video Streams	2
	Resolution	160 * 120, 320 * 240, 640 * 480
	Frame Rate	Up to 30 FPS in All Resolutions
	Min. Illumination	0.2 Lux
	Gamma	0.45
	S/N Ratio	50 dB
	Sync. Mode	Internal Sync.
	Scanning System	Progressive
	Shutter Control	NTSC: 1/60~1/100,000 sec / PAL: 1/50~1/100,000 sec
	Night Mode	AUTO
	White Balance	AWB
	Power	Power Supply
Power Consumption		Max. 5W
Audio	Audio Streaming	1 Way, MPEG2 Compression, AMR-NB for 3GPP/ISMA (RSTP)
	Audio Input / Output	Built-in Microphone
Lens	3.2 mm F2.0, viewing angle 60.3°, fixed iris	
Dimension	75(W) * 125(H) * 35(D) mm	
Weight	0.25kg	
Ingress Protection Rating	N/A	
Operating Temperature	0°C ~ 50°C	

Networking	Protocol	HTTP, TCP, UDP, ICMP, RTSP, IGMP, RTCP, SMTP, FTP, UPnP, DNS, DHCP, PPPoE
	Ethernet	10/100Mbps Fast Ethernet RJ-45 Port
	WiFi (WiFi Model Only)	IEEE 802.11g 6-54Mbps IEEE 802.11b 1-11Mbps
Software	Operating System	Windows XP and above
	Software Package	zIP View™ (36CH. Management Software)

