

GKB P6620 PnP IP Camera

Plug-and-Play Indoor Pan/Tilt CMOS IP Camera

GKB P6620 is a network-ready camera for indoor use in residential and small business surveillance installations. GKB P6620 delivers plug-and-play (PnP) networking when used with GKB zIP View™ software, and this all-in-one design features compact housing, built-in microphone, and pan/tilt mechanism.

Features:

- **Plug & Play**

GKB P6620 is a plug & play IP camera that makes network set-up easy. Once installed, set-up is as simple as entering ID and password using GKB zIP View™ software.

- **Built-in Microphone**

GKB P6620 features built-in microphone for simultaneous surveillance of video and audio.

- **3G Mobile Access**

GKB P6620 enables 3G mobile surveillance by RTSP. With mobile version NVR, surveillance is done by simply entering ID and password, on most mobile phone of Windows Mobile, Symbian, and iPhone OS.

- **MPEG4 Video Compression**

GKB P6620 features MPEG4 video compression for superior video quality. Image quality is enhanced by avoiding the conversion of analog signal to digital before transmission.

- **Pan/Tilt Mechanism**

With pan/tilt mechanism, GKB P6620 allows a wider viewing angle range, and preset positions for patrolling surveillance.

- **Micro SD Card**

GKB P6620 has a Micro SD card slot which preserves video recording in this individual storage even though the network connection is cut. .



GKB P6620 PnP IP Camera

Video	Image Sensor	1/4" CMOS
	Number of Effective Pixels	640(H) * 480(W)
	Video Compression	MPEG4
	Video Streams	2
	Resolution	160 * 120, 320 * 240, 640 * 480
	Frame Rate	Up to 30 FPS in All Resolutions
	Min. Illumination	0.2 Lux
	Gamma	0.45
	S/N Ratio	50 dB
	Sync. Mode	Internal Sync.
	Scanning System	Progressive
	Shutter Control	NTSC: 1/60~1/100,000 sec / PAL: 1/50~1/100,000 sec
	Night Mode	AUTO
	White Balance	AWB
	Power	Power Supply
	Power Consumption	Max. 10W
Audio	Audio Streaming	1 Way, MPEG2 Compression, AMR-NB for 3GPP/ISMA (RSTP)
	Audio Input / Output	Built-in Microphone
I/O Interface	DI x1, DO x1	
Storage	Micro SD card slot x1, up to 16GB Video Storage	
Pan/Tilt Control	Pan Range 130° (-65° ~ 65°), Tilt Range 90° (0° ~ 90°)	
Lens	3.2 mm F2.0, Fixed Iris	
Dimension	91(W) * 120(H) * 84(D) mm	
Weight	0.35kg	
Ingress Protection Rating	N/A	
Operating Temperature	0°C ~ 50°C	

Networking	Protocol	HTTP, TCP, UDP, ICMP, RTSP, IGMP, RTP, SMTP, FTP, UPnP, DNS, DHCP, PPPoE
	Ethernet	10/100Mbps Fast Ethernet RJ-45 Port
	WiFi	IEEE 802.11g 6-54Mbps IEEE 802.11b 1-11Mbps
Software	Operating System	Windows XP and above
	Software Package	zIP View™ (36CH. Management Software)

